



## SCHNELL SR700

### SEMI SYNTHETIC

#### PRODUCT DESCRIPTION:

SCHNELL SR700 is semi synthetic engine oil a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

#### APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

#### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Excellent protection against sludge and varnish deposits

#### PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SJ/CF

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SCHNELL SR700 (SEMI SYNTHETIC)	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	67.3	90.2
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.6	15
Viscosity Index (min)	ASTM D-2270	-	169	176
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.852	0.852
Flash Point (min)	ASTM D-92	°C	234	234
Pour Point (max)	ASTM D-97	°C	-42	-42
TBN	ASTM D-2896	Mg KOH/g	6	6
CCS, (°C)	ASTM D-5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)
			(-30°C)	

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

