



ELNINO Plus A

MINERAL

PRODUCT DESCRIPTION:

ELNINO Plus A is a multi-purpose transmission fluid, designed for use in automatic gearboxes, where GM Type A Suffix A is quoted. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.

APPLICATION:

ELNINO Plus A is suitable for use in automatic transmissions of passenger cars and light duty trucks as well as in other power shift transmissions, industrial torque converters, power steering systems and manual transmissions, where a low-viscosity fluid of GM ATF TYPE A quality is specified.

FEATURES & BENEFITS:

- Excellent oxidation stability
- High viscosity index
- Corrosion prevention
- Smoothens transmission process
- Foaming resistance
- Controlled friction properties

PERFORMANCE LEVELS: Meets or Exceeds:

- GM Type A Suffix A

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | ELNINO Plus A |
|------------------------------------|-------------|-------------------|---------------|
| Grade | | | Type A |
| Kinematic Viscosity @ 104°F /40°C | ASTM D-7042 | cSt | 52 |
| Kinematic Viscosity @ 212°F /100°C | ASTM D-7042 | cSt | 7.5 |
| Viscosity Index (min) | ASTM D-2270 | - | 106 |
| SP. Gravity @15°C/ 60°F | ASTM D-4052 | g/cm ³ | 0.885 |
| Flash Point (min) | ASTM D-92 | °C | 220 |
| Pour Point (max) | ASTM D-97 | °C | -27 |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

