



ELNINO Plus VI

SYNTHETIC

PRODUCT DESCRIPTION:

ELNINO Plus VI a fully synthetic transmission fluid recommended for use in passenger car and light truck automatic transmissions that require a GM Dexron VI or earlier generation fluid. Transmissions include the following Aisin Warner models: AW TF-80SC / SD, AWF21, AF40-6, AM6, AW6A-EI, TF81SC, AF21, GA6F21WA (Mini).

APPLICATION:

All automatic transmissions that require a GM Dexron VI or earlier generation transmission fluid. Hydraulic systems or industrial and mobile equipment operating over a wide temperature range.

FEATURES & BENEFITS:

- Meets stricter performance requirements for new GM 6 Speed automatic transmissions.
- Outstanding friction durability for consistent shift performance for the life of the fluid.
- Excellent oxidation resistance and thermal stability for long fluid life.
- Protects against sludge and varnish formation.
- Protects against wear.
- Protects against rust and corrosion
- High shear stability
- Excellent low temperature properties.
- Good seal compatibility
- Foam resistance

PERFORMANCE LEVELS: Meets or Exceeds:

- JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638 • AS 68RC (T IV) • AUDI/VW G-052-162-A1/A2
- BMW ETL-7045, 7045E, LA2634, ETL-8072B, 81 22 9 400 275 • CHRYSLER M1375.4
- FIAT (ALL VEHICLES) TYPO T-IV • GENERAL MOTORS DEXRON II/III/IIIH/VI
- HONDA ACURA Z-1 PREMIUM, HONDAMATIC S • HYUNDAI / KIA SP IV, HYUNDAI SPH-IV
- ISUZU BESCO ATF II, ATF III • JAGUAR ATF 3403 M115, JLM 20238
- LT 71141 • MAZDA ATF M III • MERCON LV • MITSUBISHI DIAMOND SP-IV
- MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41 • PEUGEOT ZF 4 HP20 • PORSCHE ATF 3403-M115
- SUBARU ATF, ATF HP • TOYOTA TYPE T-III, T-IV • TOYOTA WS • VOLVO T-IV • VOITH 55.6635 / VOLVO 97340
- ZF 5HP 18FL/19FL/24A • ZF 5HP 30 • ZFF TE-ML 09 • BMW P/N 833227542290 • CITROEN P/N PR 9980
- SAAB P/N 93165147 • TOYOTA P/N 08886-02305/08886-81015

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ELNINO Plus VI
Grade			
Kinematic Viscosity @ 104°F / 40°C	ASTM D-7042	cSt	29.5
Kinematic Viscosity @ 212°F / 100°C	ASTM D-7042	cSt	6.0
Viscosity Index (min)	ASTM D-2270	-	155
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.848
Flash Point (min)	ASTM D-92	°C	208
Pour Point (max)	ASTM D-97	°C	-48
Viscosity Brookfield @ -40 °C	ASTM-2983	mPa.s (cP)	12500

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

