



hüten 3

PRODUCT DESCRIPTION:

hüten 3 is a DOT 3 brake fluid based on poly glycol and is designed for use in hydraulic brake system of commercial vehicles, passenger cars and motorcycles operating under moderate service conditions and requiring a DOT 3 type of fluid. It provides lubricity and system protection. Also, compatible with all seals and metals used in conventional braking systems.

APPLICATION:

hüten 3 is a high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems.

FEATURES & BENEFITS

- Superior oxidative stability
- High boiling point
- Excellent low temperature fluidity ensure trouble free operation
- Effective corrosion inhibitors provide Improved life and reliability of brake system components\

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- FMVSS 116 DOT 3
- SAE J1703
- ISO 4925 Class 3

TYPICAL PERFORMANCE:

P ARAMETERS	ASTM	UNIT	hüten 3 (Typical Specification)
DRY ERBP	D-1120	°C	> 205
WET ERBP	D-1120	°C	> 140
Kinematic Viscosity @ 100C	D-445	-	> 1.5
Density @15°C	D-1298	g/cm ³	1.06
Kinematic Viscosity @ -40C	D-445	°C	< 1500
pH	D-1287	°C	7 to 11.5

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

