

# **SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking**

### **1.1 Product identifier**

Product Name:	Runol Kraftig CR Engine Oil API: CC/SC SAE 20W-50
MSDS No.:	1-0065
Product Type:	Liquid

# 1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance / Mixture:	Engine Oils
	For specific application advice see appropriate Technical Data Sheet
	or consult our company representative.

### **1.3 Details of the Supplier of the Safety Data Sheet**

Supplier:	Autotec FZE, Lot 1L Plot 20, PO Box 42540, Hamriyah Free Zone 1, Sharjah, United Arab Emirates
Supplier Phone & Email Address:	Phone: +971 6 526 2004 Email: info@autotecfze.com
Date of Issue Date of Revision Prepared by:	01-Aug-2021 15-Aug-2021 Autotec FZE

### **1.4 Emergency Telephone Number**

Emergency Telephone Number:	United Arab Emirates, Government of Sharjah, Hamriyah Free Zone
	Authority, SAFETY PHONE NO. +971 6 526 1666 (24x7)
	EMERGENCY PHONE NO. +971 6 526 2111 (24x7)

# **SECTION 2: Hazard Identification**

### 2.1 Classification of the Substance / Mixture

Product Definition:	Mixture
Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]	Not Classified
Classification according to Directive 1999/45/EC [DPD]	The product is not classified as dangerous according to Directive 1999/45/EC and its amendments. See sections 11 and 12 for more detailed information on health



effects and symptoms and environmental hazards.

### 2.2 Label Elements

Signal Word:	No signal words.
Hazard Statements:	No known significant effects or critical hazards.
Precautionary Statements:	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Supplemental Label Elements:	Not applicable.
Special Packaging Requirements:	
Containers to be fitted	Not applicable.
with child-resistant	
fastenings	
Tactile Warning of Danger:	Not applicable.

### 2.3 Other Hazards

Other Hazards which do not Result i	Defatting to the skin.
Classification:	USED ENGINE OILS
	Used engine oil may contain hazardous components, which have the
	potential to cause skin cancer.
	See Toxicological Information, section 11 of this Safety Data Sheet.

# **SECTION 3: Composition/Information on Ingredients**

Substance / Mixture:	Mixture
	Highly refined base oil (IP 346 DMSO extract < 3%). Chemically modified base oil and Proprietary performance additives.
	This product does not contain any hazardous ingredients at or above regulated thresholds.

# **SECTION 4: First Aid Measures**

# 4.1 Description of First Aid Measures

Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Eye Contact:	Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin Contact:	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical



	attention if irritation develops.
Ingestion:	
	Do not induce vomiting unless directed to do so by medical
Inholation.	personnel. Get medical attention if Symptoms occur.
Inhalation:	If isheld a second to facely also Octore final attention if any started
	If inhaled, remove to fresh air. Get medical attention if symptoms
	appear. In case of inhalation of decomposition products in a fire,
	symptoms may be delayed. The exposed person may need to be
	kept under medical surveillance for 48 hours.
Protection of First Aiders:	
	No action shall be taken involving any personal risk or without suitable training.
Protection of First Aiders:	<b>o </b> <i>i</i> <b></b> <i>i</i> <b></b>

### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed

See Section 11 for more detailed information on health effects and symptoms.

## 4.3 Indication of Immediate Medical Attention and Special Treatment Needed

Notes to Physician:	See Section 11 for more detailed information on health effects and
	symptoms.

# **SECTION 5: Fire Fighting Measures**

### 5.1 Extinguishing Media

Suitable Extinguishing Media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable Extinguishing Media	Do not use water jet.
5.2 Special Hazards Arising from Substance / Mixture	
Hazards from the Substance or	In a fire or if heated, a pressure increase will occur and the container

Mixture	may burst.
Hazardous Combustion Products	Combustion products may include the following: Carbon Oxides (CO, CO2) (carbon monoxide, carbon dioxide)

# **5.3 Advice for Fire Fighters**

Special precautions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for	Fire fighters should wear appropriate protective equipment and self-



fire-fighters

contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental Release Measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without
	suitable training. Evacuate surrounding areas. Keep unnecessary
	and unprotected personnel from entering. Do not touch or walk
	through spilt material. Floors may be slippery; use care to avoid
	falling. Put on appropriate personal protective equipment.

For emergency responders If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

### **6.2 Environmental Precautions**

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and Material for Containment and Cleaning Up

Small Spill	Stop leak if without risk. Move containers from spill area. Absorb with
	an inert material and place in an appropriate waste disposal
	container. Dispose of via a licensed waste disposal contractor.

Large Spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, watercourses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

### **6.4 Reference to Other Sections**

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.



# **SECTION 7: Handling and Storage**

### 7.1 Precautions for safe handling

Protective measures Put on appropriate personal protective equipment.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabeled containers.

### 7.3 Specific and End Use(s) Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

# **SECTION 8: Exposure Controls / Personal Protection**

### **8.1 Control Parameters**

Occupational Exposure Limits	No exposure limit value known measures.	
	Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.	
Recommended Monitoring Procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical agents) European	



Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level No DNELs/DMELs available

Predicted No Effect Concentration No PNECs available.

### **8.2Exposure Controls**

Appropriate Engineering Controls Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organization for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible. Individual protection measures Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location. **Respiratory Measures** Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures

should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Eye / Self Protection Safety glasses with side shades Skin Protection Hand Protection General Information: Because specific work environments and material handling practices vary, safety procedures should be developed for each intended



application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures). Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile Gloves

#### Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are considered. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes must be determined and rigorously followed.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks.

For Example:

• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and Body: Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and



Refer to Standards

boots will be required.

Environmental Exposure Controls

Respiratory protection: EN529 Gloves: EN420, EN374 Eye protection: EN166

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and Chemical Properties**

# 9.1 Information on Basic Physical and Chemical Properties

Physical StateLiquidColorLight AmberOdorTypical PetroleumOdor thresholdNot AvailablepHNot AvailableMelting point/freezing pointNot AvailableInitial boiling point and boiling rangeNot AvailablePour point-24 °C
OdorTypical PetroleumOdor thresholdNot AvailablepHNot AvailableMelting point/freezing pointNot AvailableInitial boiling point and boiling rangeNot Available
Odor thresholdNot AvailablepHNot AvailableMelting point/freezing pointNot AvailableInitial boiling point and boiling rangeNot Available
pHNot AvailableMelting point/freezing pointNot AvailableInitial boiling point and boiling rangeNot Available
Melting point/freezing point     Not Available       Initial boiling point and boiling range     Not Available
Initial boiling point and boiling range Not Available
Pour point 24 °C
Pour point -24 °C
Flash point 230 °C
Evaporation rate Not Available
Flammability (solid, gas) Not Available
Upper/lower flammability or Not Available
explosive limits
Vapor pressure Not Available
Vapor density Not Available
Relative density Not Available
SP. Gravity @15°C/ 60°F 0.887 g/cm <sup>3</sup>
Solubility Insoluble in water.
Partition coefficient: Not Available
Auto-ignition temperature Not Available
Decomposition temperature Not Available
Viscosity Kinematic Viscosity 24.2 cSt @ 212°F /100°C
Explosive properties Not Available
Oxidizing properties Not Available

# 9.2 Other Information

No Additional Information

# **SECTION 10: Stability and Reactivity**



### 10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

### **10.2Chemical Stability**

This product is stable.

### **10.3Possibility of Hazardous Reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

**10.4Conditions to Avoid** 

Avoid all possible sources of ignition (spark or flame).

### **10.5Incompatible Materials**

Reactive or incompatible with Oxidizing Materials

### **10.6Hazardous Decomposition Products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological Information**

### **11.2Information on Toxicological Effects**

Acute Toxicity Estimates Petroleum derived calcium salt 61789-86-4	<b>Route</b> Oral Dermal Inhalation (dusts and mists)	ATE Value > 5000mg/kg > 4000 mg/kg 418.6 mg/l
Information on the likely routes of exposure	Routes of entry anticipated: Derr	nal, Inhalation.
Potential Acute Health Effects Inhalation	Exposure to decomposition pro Serious effects may be delayed f	ducts may cause a health hazard. following exposure.



Ingestion	No known significant effects or critical hazards.		
Skin Contact	Defatting to the skin. May cause skin dryness and irritation.		
Eye Contact	No known significant effects or critical hazards.		
Symptoms related to the physical, chemical and toxicological characteristics Inhalation Ingestion Skin Contact Eye Contact	No specific data No specific data Adverse symptoms may include irritation, dryness, cracking No specific data		
Delayed and immediate effects and also chronic effects from short- and long-term exposure Inhalation/Ingestion Skin Contact Potential Chronic Health Effects	Over exposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion of large quantities may cause nausea and diarrhea. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Potential risk of transient stinging or redness if accidental eye contact occurs.		
General	Used Engine Oils: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components, which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.		
Carcinogenicity	No know significant effects or critical hazards.		
Mutagenicity	No know significant effects or critical hazards.		
Developmental Effects	No know significant effects or critical hazards.		
Fertility Effects	No know significant effects or critical hazards.		



# **SECTION 12: Ecological Information**

### 12.1 Toxicity

Environmental Hazard

Not classified as dangerous.

### 12.2Persistence and Degradability

Partially biodegradable.

### **12.3Bio Accumulative Potential**

This product is not expected to bio accumulate through food chains in the environment.

### 12.4Mobility in Soil

Soil / Water partition coefficient (KOC)	Not available						
Mobility	Spillages may contamination	penetrate	the	soil	causing	ground	water

### 12.5Result of PBT and vPVB Assessment

Not applicable

vPVB Not applicable

### **12.60ther Adverse Effects**

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

# **SECTION 13: Disposal Considerations**

### **13.1Waste Treatment Methods**

Methods of Disposal		product to be recycled. Dispose of via insed waste disposal contractor in ons.
	Waste Code	Waste Designation
	13 02 08*	Other engine, gear, and lubricating oils
		ntended use and/or the presence of a require an alternative waste disposal



code to be assigned by the end user.

Packing Methods of Disposal	Where possible, arrange for product to be recycled. Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.
Special Precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport Information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN Number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN Proper Shipping Name	-	-	-	-
14.3 Transport Hazard Class	-	-	-	-
14.4 Packing Group	-	-	-	-
14.5 Environmental Hazards	NO	No	No	No
Additional Information	-	-	-	-
14.6 Special Precautions for User	Not available			

# **SECTION 15: Regulatory Information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization	None of the components are listed
Substances of very high concern Annex XVII - Restrictions on the manufacturer, placing on the market and use of certain dangerous substances, mixtures and articles.	Not applicable
Other Regulations REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
United States Inventory (TSCA 8b) Australia Inventory (AICS)	All components are listed or exempted. At least one component is not listed.



Canada Inventory China Inventory (IECSC) Japan Inventory (ENCS) Korea Inventory (KECI) Philippines Inventory (PICCS) At least one component is not listed. At least one component is not listed.

### **15.2Chemical Safety Assessment**

This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other Information**

Abbreviations and Acronyms	Waterway ADR = The Europ ATE = Acute Tox BCF = Bio Conce CAS = Chemical CLP = Classificat CSR = Chemical DMEL = Derived DMEL = Derived IMECS = Europ ES = Exposure S EUH statement = EWC = Europear GHS = Globally F IATA = Internatio IBC = Intermedia IMDG = Internatio LogPow = logarit MARPOL 73/78 = by the Protocol of OECD = Organiz PBT = Persistent PNEC = Predicte RID = The Regul RRN = REACH R SADT = Self-Acc SVHC = Substan STOT-RE = Spec TWA = Time weig UN = United Nati UVCB = Complex VOC = Volatile O	bean Agreement concerning the Inter- icity Estimate entration Factor Abstracts Service ion, Labeling and Packaging Regula Safety Assessment Safety Report Minimal Effect Level No Effect Level s Preparations Directive [1999/45/E s Substances Directive [67/548/EEC ean Inventory of Existing Commerci cenario CLP-specific Hazard statement to Waste Catalogue Harmonized System of Classification nal Air Transport Association te Bulk Container onal Maritime Dangerous Goods hm of the octanol/water partition code = International Convention for the Pl f 1978. ("Marpol" = marine pollution) ation for Economic Co-operation an , Bio Accumulative and Toxic d No Effect Concentration ations concerning the International C egistration Number elerating Decomposition Temperatu ces of Very High Concern offic Target Organ Toxicity - Repeate ific Target Organ Toxicity - Single E ghted average	2) al chemical Substances a and Labeling of Chemicals efficient revention of Pollution from Ships, 1973 as modified d Development Carriage of Dangerous Goods by Rail re ed Exposure
Full text of abbreviate statements Full text of classificat [CLP/GHS]		H 304 H 413 Aquatic Chronic 4, H413 Asp. Tox. 1, H304	May be fatal if swallowed and enters airways. May cause long lasting harmful effects to aquatic life. LONG-TERM AQUATIC HAZARD - Category 4



#### ASPIRATION HAZARD Category 1

Full text of abbreviated R Phrases	R53-	May	cause	long-term	adverse	effects	in	the	aquatic
	environment.								

Full text of classifications [DSD/DPD

Not Applicable

History

Date of Issue	01-Aug-2021
Date of Revision	15-Aug-2021
Prepared by:	Autotec FZE

### Notice to Reader:

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from Autotec FZE. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Autotec FZE shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the Autotec FZE to ensure that this document is the most current available. Alteration of this document is strictly prohibited.