



## ELNINO PLUS 4

### SYNTHETIC

#### PRODUCT DESCRIPTION:

ELNINO PLUS 4 automatic transmission fluid is designed for use in most types of Japanese, Korean, and Chrysler vehicles that require ATF+4 or prior specifications. This chemistry offers excellent low temperature properties and improved anti-shudder properties. ELNINO PLUS 4 is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying Chrysler ATF+4, ATF+3 or ATF+2 type fluids.

#### FEATURES & BENEFITS:

- Excellent flow properties at low start-up temperatures and high operating temperatures
- Improved shift performance and vehicle drivability/improved shudder performance
- Good viscosity stability
- Excellent oxidation stability, less fluid breakdown in high-temperature service
- Dependable protection against rust and corrosion
- Provides more assured wear protection for maximum transmission/transaxle life
- Engineered with superior base oils to ensure superb low and high temperature performance

#### APPLICATION:

- Automatic transmissions specially formulated for Chrysler vehicles, including Dodge, Plymouth, Eagle and certain Jeeps, that require a fluid meeting ATF+4 specification.
- Mitsubishi and Hyundai applications where an MS-9602 type fluid is specified.
- Services that specify a ATF+, ATF+2 and ATF+3 type fluid, including certain manual transmissions, transfer cases and power steering units (1999 and later).

#### PERFORMANCE LEVELS: Meets or Exceeds:

- Chrysler ATF+4® Requirements
- Chrysler MS-9602

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ELNINO PLUS 4
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	31.79
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7.30
Viscosity Index (min)	ASTM D-2270	-	205
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.839
Flash Point (min)	ASTM D-92	°C	198
Pour Point (max)	ASTM D-97	°C	-51
Viscosity Brookfield @ -40 °C	ASTM D2983	mPa.s (cP)	8400

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

