



KRAFTIG CR 5 MINERAL

PRODUCT DESCRIPTION:

KRAFTIG CR 5 is a high performance heavy duty engine oil based on high quality mineral base stocks and advance additives trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. It is recommended for automotive diesel engine of passenger cars and light commercial vehicles where the OEM recommends API CF-4 or earlier specification.

APPLICATION:

Recommended for modern heavy duty engines, wide range of turbo-charged or naturally aspirated diesel engines, generators, trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. It is recommended for automotive diesel engine of passenger cars and light commercial vehicles where the OEM recommends API CF-4 or earlier specification.

FEATURES & BENEFITS:

- Fuel saving and reduces maintenance expenses for machines and engines.
- Very long oil changing period.
- Resists oil thickening and the formation of carbon, varnish and sludge deposits.
- Good viscosity control.
- Prolonged engine life.
- Safeguards the moving parts.
- Keeps engine Clean.
- API CF-4/SJ
- MB 228.2
- ACEA E2-96, A3/B3
- MTU Type-2
- MAN 3275-1
- VOLVO VDS
- MACK E0/K2
- CES 20075/74/73

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	KRAFTIG CR 5 (MINERAL)					
			15W-40	15W-50	20W-50	20W-60	40	50
Grade			15W-40	15W-50	20W-50	20W-60	40	50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	116.15	109.5	175.35	201.05	151.4	214.15
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	15.35	15.2	19.80	24.2	15.5	20.2
Viscosity Index (min)	D-2270	-	139	146	131	150	105	110
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.881	0.878	0.891	0.887	0.895	0.896
Flash Point (min)	D-92	°C	236	232	236	230	242	246
Pour Point (max)	D-97	°C	-33	-33	-24	-24	-15	-15
TBN	D-2896	Mg KOH/g	9	9	9	9	9	9
CCS, (°C)	D-5293	m.Pa.S	<7000 (-20°C)	<7000 (-20°C)	<9500 (-15°C)	<9500 (-15°C)	-	-

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Runol.net

